

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/075808 A1

(51) International Patent Classification⁷: **F02M 35/06**,
35/08, F01P 11/12, F04D 17/08, B01D 35/22

(74) Agent: **FRASER OLD & SOHN**; Patent Attorneys, Level
6, 118 Alfred Street, Milsons Point, NSW 2061 (AU).

(21) International Application Number:
PCT/AU2005/000136

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 2 February 2005 (02.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004 900 510 4 February 2004 (04.02.2004) AU
2004 904 647 16 August 2004 (16.08.2004) AU


(71) Applicants and

(72) Inventors: **NOTARAS, John, Arthur** [AU/AU]; 9 Fred
Street, Lilyfield, NSW 2040 (AU). **NOTARAS, Angelo,
Lambrinos** [AU/AU]; 9 Fred Street, Lilyfield, NSW 2040
(AU).

(81) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: AIR FILTER ARRANGEMENT



(57) Abstract: A self cleaning filter
for a small internal combustion
engine (1) is disclosed. The filter
(16, 36, 46) is generally rectangular
and is located closely adjacent
the air exit region of the engine's
fan (2). The longitudinal axis
of the filter is generally aligned
with the direction of air flow. The
filter can be flat (16), curved (36)
or inclined towards the air flow
(46). The arrangement permits a
more compact configuration for the
engine (1).



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*